


# General type stator winding RTD

## Model : R830 series

Spec. sheet no. RD08-03

### Service intended

The purpose of the stator winding RTD is to mainly detect and prevent overheating of motors. It is inserted between a stator and a slot to measure a temperature. Stator winding RTD uses the phenomenon of changing electric resistance to measure a temperature. Since it has high stability and sensitivity, it is used to measure a temperature precisely. Furthermore, it is made of a nonmetallic material, and, therefore, it has a structure of protecting element. It is designed well enough to get flexibility and to endure vibration and high pressure.



### Standard features

#### Body material

High temperature epoxy glass

#### Temperature limit

Class F : 155 °C (311 °F)

Class H : 180 °C (356 °F)

#### Lead wires

3 wire or 4 wire, copper, AWG #22 (With FEP or polyimide insulation)

#### Ambient temperature

Tamb = -50 ~ 180 °C

#### Working temperature

-50 ~ 180 °C

## Main order

## Ordering information

### 1. Base model

- R831** RTD single element - 3 wire
- R832** RTD double element - 6 wire
- R833** RTD single element - 3 wire with shield wire
- R834** RTD double element - 6 wire with shield wire
- R835** RTD single element - 4 wire
- R836** RTD double element - 8 wire
- R837** RTD single element - 4 wire with shield wire
- R838** RTD double element - 8 wire with shield wire

### 2. Explosion proof type

- N** N/A

### 3. Element

- 1** Platinum (0.00385 TCR), Class "AA" - EN 60751
- 2** Platinum (0.00385 TCR), Class "A" - EN 60751
- 3** Platinum (0.00385 TCR), Class "B" - EN 60751
- 0** Other

### 4. Temperature limited

- F** Class F, 155 °C (311 °F)
- H** Class H, 180 °C (356 °F)

### 5. Body thickness

- A1** 0.079" (2.0 mm)

### 6. Body length (mm)

- 1** 6 (W) x 155 (L) - Single element
- 2** 11 (W) x 155 (L) - Double element
- 0** Other - Min. 6 (W) ~ Max. 14 (W) x Min. 155 (L)

### 7. Lead wire insulation

- F** FEP
- O** Other

### 8. Lead wire length (m)

- L1** 1
- L2** 2
- L3** 3
- L4** 4
- L5** 5
- L0** Other (Min. 300 mm)

### 9. Lead wire color

- E** EN code
- K** KS code
- Z** Other

### 10. Option

- T** Twisted type lead wire
- Z** Other

1	2	3	4	5	6	7	8	9	10
R831	N	2	H	A1	1	F	L3	K	T

Sample  
ordering code