Special Pressure Gauge

Model No. SS-3020 Series



Ordering Information

SS-3021 × 100mm × 0~1MPa × PF3/8

CONNECTION:

- UNF7/16 (Not available 40mm, 50mm, 150mm, 200mm)
- PF1/8 (Not available 150mm, 200mm)
- NPT&PT1/8 (Not available 150mm, 200mm)
- PF1/4 (Not available 150mm, 200mm, 40mm)
- NPT&PT1/4 (Not available 150mm, 200mm, 40mm)
- PF3/8 (Not available 60mm, 40mm, 50mm)
- NPT&PT3/8 (Not available 60mm, 40mm, 50mm)PF1/2 (Not available 60mm, 75mm, 40mm, 50mm)
- NPT&PT1/2 (Not available 60mm, 75mm, 40mm, 50mm)

RANGE:

 $-40 \, \mathrm{mm}$: 0.2 $\sim 25 \, \mathrm{MPa}$ $-50 \, \mathrm{mm}$: 0.2 $\sim 25 \, \mathrm{MPa}$

- NOMINAL DIAMETER & ACCURACY:

- 40mm (Accuracy: ±3.0% of Full Scale)
- 50mm (Accuracy: ±1.5% of Full Scale)
- 60mm (Accuracy: $\pm 1.5\%$ of Full Scale)
- 75 mm (Accuracy: ±1.5% of Full Scale)
- 100mm (Accuracy: ±1.0% of Full Scale)
- 150 mm (Accuracy: ±1.0% of Full Scale)
- 200mm (Accuracy: ±1.0% of Full Scale)

- BASE MODEL & MOUNTING TYPE:

- SS-3021(A:Rimless type) : Bottom Connection, Direct
- SS-3022 (B:Surface type): Bottom Connection, Surface
- SS-3023 (D:Flush mounting type) : Lower Back Connection, Direct
- SS-3024 (BD:Panel attachment type) : Lower Back Connection, Flush
 - ▶ 200mm : Only available with SS-3022, SS-3024



Special Pressure Gauge

Model No. SS-3020 Series





SS-3021



SS-3024

Summary

This gauge has high corrosive resistance and it is properly built to measure fluid pressure which can withstand outside condition change. It has high accuracy because its connecting part is made of stainless steel.

Safety Management

- Be sure to install a protecting device where exist abrupt change of pressure, vibration and pulsation.
- Do not give impact during the transportation, installation and usage,
- Be sure to install pressure gauge to be horizontal and vertical

Production Specification

· 40, 50, 60, 75, 100, 150 mm

Accuracy

- · 40mm: ±3% of Full Scale
- · 50mm이상: ±1.5% of Full Scale
- \cdot 100, 150mm : $\pm 1.0\%$ of Full Scale

▶ Working Pressure

- · Static pressure: 75% of Full Scale
- · Fluctuating pressure: 60% of Full Scale

▶ Working Temperature

- · Ambient : 20 \sim 65 °C
- · Fluid : 20 \sim 80 $^{\circ}\mathrm{C}$
- ▶ Degree of Protection · IP67

▶ Range

40mm 50mm	0.2 ∼ 25 MPa
60mm 75mm	- 0.1 ~ 2 MPa - 0.1 ~ 0 MPa 0 ~ 35 MPa
100mm 150mm	- 0.1 ~ 2 MPa - 0.1 ~ 0 MPa 0 ~ 200 MPa

Purpose of Use

- Various plants such as petrochemistry, etc. (corrosive atmosphere, steam, place where exists a lot of dust, outdoor)
- Special fluid line for industrial use.

Product Specification

- + Case
 - STS 304
- + Cover
 - STS 304 Slip-on-Fit
- + Connection


 - · PF. PT. NPT ↔ 1/4, 3/8, 1/2
 - · UNF 7/16
- + Window
 - · Tempered safety glass, Laminated safety glass

- - A-Type (Rimless type)
 - B-Type (Surface type)
 - D-Type (Flush mounting type)
- · BD-Type(Panel attachment type)
- + Pointer
 - · Aluminum
- Black coating
- - Aluminum
 - White color coating
 - · Black (MPa), red (bar) gradations and characters


- + Element
 - STS 304, STS 316
 - · C type bourdon tube, helical type bourdon tube
- + Movement
 - STS 304
- + Option
 - · Blow out protection on the Top Rubber Disc
 - Bracket
 - · Throttles
 - · Accessories

Model No. SS-3020 Series


Model No. | SS-3021 A Type (60, 75, 100, 150mm)




Model No. | SS-3023 D Type (60, 75, 100, 150mm)




Model No. | SS-3022 B Type (60, 75, 100, 150mm)




Model No. | SS-3024 BD Type (60, 75, 100, 150mm)



Model No. | SS-3021 A Type (40, 50mm)



Model No. | SS-3023 D Type (40, 50mm)





Dimensions (mm)

	Model No.	Conn'n (d)	ØD	ØD1	ØD2	b	n	t	L2	h	ØС	ØН
40mm	SS-3021	NPT & PT, PF 1/8	46.2	41	_	7.5	_	(26.5)	12	(26.5)	_	_
	SS-3023	NPT & PT, PF 1/8	46.2	41	_	_	_	(26.5)	12	(7.5)	_	_
50mm	SS-3021	NPT & PT, PF 1/8	- 58.2	51.7	_	9.5	_	(30)	14	(35.5)	-	_
		NPT & PT, PF 1/4										
	SS-3023	NPT & PT, PF 1/8	- 58.2	51.7	_	-	_	(30)	14	(7.5)	-	_
		NPT & PT, PF 1/4										
60mm	SS-3021 & SS-3022	UNF 7/16	72	64	84	12	_	(39)	12	(48)	4.5	72
		NPT & PT, PF 1/8										
		NPT & PT, PF 1/4										
	SS-3023 & SS-3024	UNF 7/16	72	64	90	_	17	(39)	12	(20)	4.5	81
		NPT & PT, PF 1/8										
		NPT & PT, PF 1/4										
	SS-3021 & SS-3022	UNF 7/16	87	77	100	14	_	(40)	14	(54)	4.5	88
		NPT & PT, PF 1/4										
7E		NPT & PT, PF 3/8										
75mm	SS-3023 & SS-3024	UNF 7/16	87	77	107	-	22	(40)	14	(17)	4.5	97
		NPT & PT, PF 1/4										
		NPT & PT, PF 3/8										
100mm	SS-3021 & SS-3022	UNF 7/16	- 114	100	128	17	_	(46)	17	(76)	5.5	115
		NPT & PT, PF 1/4										
		NPT & PT, PF 3/8										
		NPT & PT, PF 1/2										
	SS-3023 & SS-3024	UNF 7/16	114	100	135	_	33	(46)	17	(26)	5.5	120
		NPT & PT, PF 1/4										
		NPT & PT, PF 3/8										
		NPT & PT, PF 1/2										
150mm	SS-3021 & SS-3022	UNF 7/16	168	152	188	17	_	(50)	17	(100)	5.5	174
		NPT & PT, PF 1/4										
		NPT & PT, PF 3/8										
		NPT & PT, PF 1/2										
	SS-3023 & SS-3024	UNF 7/16	168	152	188	_	33	(50)	17	(26)	5.5	174
		NPT & PT, PF 1/4										
		NPT & PT, PF 3/8										
		NPT & PT, PF 1/2										

^{*()}The measurement in the blanket is approximate.